

# Technical Data Sheet

## StoDivers UR

Maintenance cleaning agent for floor coatings  
already treated with a floor finish



### Characteristics

- Area of application**
- For interior and external application
  - As a maintenance cleaner on Sto floor coating systems treated with StoDivers P 105 / 110 / 120
  - As a maintenance cleaner for floor coatings

### Properties

- Due to a neutral formulation, streak-free cleaning is possible without affecting the gloss
- The low-foaming adjustment means it can be used in all floor scrubber dryers
- Rapid-drying

### Technical Data

Criteria	Standard / test specification	Value / Unit	Notes
Density	EN ISO 2811	1.0 g/cm <sup>3</sup>	
pH Value		8.5	

The characteristic values stated are average values or approximate values. Due to the natural raw materials in our products, the stated values can vary slightly in the same delivery batch; this does not affect the suitability of the product for its intended use.

### Substrate

**Requirements** The substrate must be free from loose and coarse dirt.

### Application

**Application temperature** Lowest application temperature: +8°C  
Highest application temperature: +30°C

**Time for application** Depends on the degree of soiling

**Mixing Ratio** Manual cleaning: 50 – 100 ml for 10L of water  
Cleaning by machine: 100 – 200 ml for 10L of water

### Application

With a mop or floor scrubber dryer

#### Manual cleaning:

Dilute StoDivers UR with approx. 50 – 100 ml to 10L of cold water in a pail. Clean the floor using a clean mop and collect any loosened dirt.

#### Cleaning by machine:

Depending on the degree of soiling, dilute StoDivers UR with approx. 100 – 200 ml to 10L of cold water into the tank of floor scrubber dryer. Go over the surface with the floor scrubber dryer and suction up the waste water at the same time.

For stubborn soiling, first leave the cleaning solution to react for approx. 5 minutes, then scrub or suction clean the floor.

### Cleaning the tools

Tools must be cleaned immediately after use with clean water

# Technical Data Sheet

## StoDivers UR

**Notes, recommendations, special information, miscellaneous** Please consult the local sales office for further information and any site assistance required.

### Delivery

Packaging	Name	Container
	StoDivers UR	5 lit

### Storage

<b>Storage conditions</b>	Store in cool dry conditions; avoid direct sunlight.
<b>Storage life</b>	This product has a shelf life of 48 months from the manufacturing date.

### Identification

<b>Product group</b>	Supplementary & Maintenance Products
----------------------	--------------------------------------

### Safety

Please refer to Safety Data Sheet.

### Special Notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on [www.sto-sea.com](http://www.sto-sea.com).

**Sto SEA Pte Ltd**  
 159 Sin Ming Road  
 #06-02 Amtech Building  
 Singapore 575625  
 Phone: +65 6453 3080  
 Fax : +65 6453 3543  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**Sto SEA Sdn Bhd**  
 28, Jalan Rajawali 3  
 Bandar Puchong Jaya,  
 47170 Selangor, Malaysia  
 Phone: +60 3 8080 9066  
 Fax: +60 3 8080 9255  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**Sto SEA Pte Ltd**  
 3656/49-52 Green Tower, 16<sup>th</sup> Floor  
 Rama IV Rd, Klongton, Klongtoei,  
 10110 Bangkok, Thailand  
 Phone: +66 2 1684 921 Ext. 230  
 Fax: +66 2 1684 999  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**StoCretec GmbH**  
 Gutenbergstr. 6  
 65830 Kriftel,  
 Germany  
 Phone: +49 6192 401 104  
 Fax: +49 6192 401 105  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

\*Product images may differ from the actual product.