

Technical Data Sheet

StoQuarz AS

Quartz sand mixture, graduated grain size



Characteristics

- Area of application**
- As extender for producing epoxy resin mortars and screeds
 - Optimised grain size mix for minimising binding agent consumption

- Properties**
- Maximum particle size: 3 mm

Delivery

Packaging	Name	Container
	StoQuarz AS	20 kg bag

Special Notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on www.sto-sea.com.

Sto SEA Pte Ltd
 159 Sin Ming Road
 #06-02 Amtech Building
 Singapore 575625
 Phone: +65 6453 3080
 Fax : +65 6453 3543
info.sg@sto.com
www.sto-sea.com

Sto SEA Sdn Bhd
 28, Jalan Rajawali 3
 Bandar Puchong Jaya,
 47170 Selangor, Malaysia
 Phone: +60 3 8080 9066
 Fax: +60 3 8080 9255
info.my@sto.com
www.sto-sea.com

Sto SEA Pte Ltd
 3656/49-52 Green Tower, 16th Floor
 Rama IV Rd, Klongton, Klongtoei,
 10110 Bangkok, Thailand
 Phone: +66 2 1684 921 Ext. 230
 Fax: +66 2 1684 999
info.sg@sto.com
www.sto-sea.com

StoCretec GmbH
 Gutenbergstr. 6
 65830 Kriftel,
 Germany
 Phone: +49 6192 401 104
 Fax: +49 6192 401 105
info.sg@sto.com
www.sto-sea.com

*Product images may differ from the actual product.