

Technical Data Sheet

StoQuarz Conduct

Quartz sand, electrically conductive



Characteristics

Area of application ■ As scatter material for achieving electrically conductive properties in combination with increased slip resistance

Delivery

Colour shade	Black		
Packaging	Article no.	Name	Container
	03731-001	StoQuarz Conduct black 0.3 – 0.8 mm	25 kg bag

Storage

Storage conditions Store in cool dry conditions

Identification

Product group Supplementary Products

Safety Please refer to Safety Data Sheet.

Special Notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on www.sto-sea.com.

Sto SEA Pte Ltd
159 Sin Ming Road
#06-02 Amtech Building
Singapore 575625
Phone: +65 6453 3080
Fax: +65 6453 3543
info.sg@sto.com
www.sto-sea.com

Sto SEA Sdn Bhd
28, Jalan Rajawali 3
Bandar Puchong Jaya,
47170 Selangor, Malaysia
Phone: +60 3 8080 9066
Fax: +60 3 8080 9255
info.my@sto.com
www.sto-sea.com

Sto SEA Pte Ltd
3656/49-52 Green Tower, 16th Floor
Rama IV Rd, Klongton, Klongtoei,
10110 Bangkok, Thailand
Phone: +66 2 1684 921 Ext. 230
Fax: +66 2 1684 999
info.sg@sto.com
www.sto-sea.com

StoCretec GmbH
Gutenbergstr. 6
65830 Kriftel,
Germany
Phone: +49 6192 401 104
Fax: +49 6192 401 105
info.sg@sto.com
www.sto-sea.com

*Product images may differ from the actual product.