

# Technical Data Sheet

## Sto-Siliciumcarbid

Silicon carbide, electrically conductive



### Characteristics

- Area of application**
- As scatter material for achieving electrically conductive properties in combination with increased slip resistance
  - As scatter material for selected façade finishes

### Appearance

- Gloss

### Delivery

**Colour** Black

### Packaging

Article no.	Name	Container
00191-001	Sto Siliciumcarbid F 36, approx. grain size 0.40 - 0.60 mm	25 kg bag
00190-001	Sto Siliciumcarbid F 24, approx. grain size 0.60 - 0.85 mm	25 kg Bag
14219-002	Sto Siliciumcarbid F 14, approx. grain size 1.20 - 1.70 mm	25 kg Bag
14218-002	Sto Siliciumcarbid F 20, approx. grain size 0.85 - 1.20 mm	25 kg Bag
14217-002	Sto Siliciumcarbid F 54, approx. grain size 0.25 - 0.35 mm	25 kg Bag

### Storage

**Storage conditions** Store in cool dry conditions

### Identification

**Product group** Supplementary Products

### Safety

Please refer to Safety Data Sheet.

# Technical Data Sheet

## Sto-Siliciumcarbid

### Special Notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on [www.sto-sea.com](http://www.sto-sea.com).

**Sto SEA Pte Ltd**  
159 Sin Ming Road  
#06-02 Amtech Building  
Singapore 575625  
Phone: +65 6453 3080  
Fax: +65 6453 3543  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**Sto SEA Sdn Bhd**  
28, Jalan Rajawali 3  
Bandar Puchong Jaya,  
47170 Selangor, Malaysia  
Phone: +60 3 8080 9066  
Fax: +60 3 8080 9255  
[info.my@sto.com](mailto:info.my@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**Sto SEA Pte Ltd**  
3656/49-52 Green Tower, 16<sup>th</sup> Floor  
Rama IV Rd, Klongton, Klongtoei,  
10110 Bangkok, Thailand  
Phone: +66 2 1684 921 Ext. 230  
Fax: +66 2 1684 999  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**StoCretec GmbH**  
Gutenbergstr. 6  
65830 Kriftel,  
Germany  
Phone: +49 6192 401 104  
Fax: +49 6192 401 105  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

\*Product images may differ from the actual product.