

Technical Data Sheet

StoDivers GR

Stripper for epoxy / polyurethane floor coatings



Characteristics

- Area of application**
- Interior areas and areas exposed to weathering
 - Suitable for removing old polymer and wax layers
 - Suitable for removing dirt accumulations on Sto floor and balcony coatings

Properties

- Removes old care treatment layers quickly and thoroughly
- Saves up to 50% working time, because rinsing or neutralising afterwards is not required
- Good adhesion to subsequent floor finishes with StoDivers P 105 / 110 / 120
- Water-based

Technical Data

Criteria	Standard / test specification	Value / Unit	Notes
Density	EN ISO 2811	1.0 g/cm ³	
Viscosity	EN ISO 3219	< 5 mPa.s	
pH Value		13.0 - 14.0	

The characteristic values stated are average values or approximate values. Due to the natural raw materials in our products, the stated values can vary slightly in the same delivery batch; this does not affect the suitability of the product for its intended use.

Application

Application temperature	Lowest application temperature: +8°C Highest application temperature: +30°C
Time for application	Depends on the degree of soiling.
Mixing ratio	StoDivers GR : water = 25.0 : 100 to 12.4 : 100 parts by weight
Coating build-up	StoDivers GR basic cleaner

Application

Commercially - available cleaning equipment

StoDivers GR basic cleaner

StoDivers GR can be used on all StoCretec floor coating systems.

If using on StoCryl BF 100, StoPox WL 100/100 transparent or StoPox WB 100/110, check the colour-fastness/compatibility beforehand, particularly with special colour shades.

Depending on the layer build-up of the dirt or wax layer, dilute StoDivers GR 25.0 : 100 to 12.4 : 100 with cold water.

Use a mop to spread the solution evenly and generously onto the floor and leave it to react for 5 - 10 minutes.

Technical Data Sheet

StoDivers GR

Scrub the floor using a single- disc machine with a suitable pad, and collect the loosened dirt using a wet vacuum cleaner. If necessary, repeat the procedure several times.

Remove any seams with a mop. Leave the floor to dry thoroughly. It is not necessary to rinse afterwards with clear water.

Apply StoDivers P 105 / StoDivers P 120 in accordance with the relevant Technical Data Sheet.

Cleaning the tools Clean with water.

Notes, recommendations, special information, miscellaneous Please consult the local sales office for further information and any site assistance required.

Delivery

Packaging	Name	Container
	StoDivers GR	5 lit

Storage

Storage conditions Store in cool dry conditions; avoid direct sunlight.

Storage life This product has a shelf life of 48 months from the manufacturing date.

Identification

Product group Supplementary & Maintenance Products

Safety Please refer to Safety Data Sheet.

Special Notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on www.sto-sea.com.

Sto SEA Pte Ltd
159 Sin Ming Road
#06-02 Amtech Building
Singapore 575625
Phone: +65 6453 3080
Fax : +65 6453 3543
info.sg@sto.com
www.sto-sea.com

Sto SEA Sdn Bhd
28, Jalan Rajawali 3
Bandar Puchong Jaya,
47170 Selangor, Malaysia
Phone: +60 3 8080 9066
Fax: +60 3 8080 9255
info.sg@sto.com
www.sto-sea.com

Sto SEA Pte Ltd
3656/49-52 Green Tower, 16th Floor
Rama IV Rd, Klongton, Klongtoei,
10110 Bangkok, Thailand
Phone: +66 2 1684 921 Ext. 230
Fax: +66 2 1684 999
info.sg@sto.com
www.sto-sea.com

StoCretec GmbH
Gutenbergstr. 6
65830 Kriftel,
Germany
Phone: +49 6192 401 104
Fax: +49 6192 401 105
info.sg@sto.com
www.sto-sea.com

*Product images may differ from the actual product.