

# **Technical Data Sheet**

## StoDivers LB 100

Conductive copper tape, tin-plated



Characteristics		
Area of application	For the connection to the ring line on electrically conductive floor coatings	
Properties	<ul> <li>Self-adhesive</li> </ul>	
Information/notes	<ul><li>Width: 12 mm</li><li>Length: 16.5 m</li></ul>	
Application		
Consumption	Execution	Approx. consumption
	loose, width	12 mm, length : 16.5 m
	Material consumption depends on the application, substrate, and consistency, among other factors. The stated consumption values are only to be used as a guide. If required, determine precise consumption values on the basis of the specific project.	
Delivery		
Packaging	Name	Container
	StoDivers LB 100	1 piece
Identification		
Product group	Supplementary & Maintenance Products	
Special Notes		
	The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.	
	after prior consultation. Whe	nentioned in this Technical Data Sheet are permissible only re no approval is given, such applications are at the user's ticular when the product is used in combination with other
	•	

## Sto SEA Pte Ltd

159 Sin Ming Road #06-02 Amtech Building Singapore 575625 Phone: +65 6453 3080 +65 6453 3543 Fax: info.sg@sto.com www.sto-sea.com

## Sto SEA Sdn Bhd

28, Jalan Rajawali 3 Bandar Puchong Jaya, 47170 Selangor, Malaysia Phone: +60 3 8080 9066 Fax: +60 3 8080 9255 info.sg@sto.com www.sto-sea.com

## Sto SEA Pte Ltd

3656/49-52 Green Tower, 16th Floor Rama IV Rd, Klongton, Klongtoei, 10110 Bangkok, Thailand Phone: +66 2 1684 921 Ext. 230 +66 2 1684 999 Fax:

## info.sg@sto.com www.sto-sea.com

#### StoCretec GmbH

Gutenbergstr. 6 65830 Kriftel, Germany

Phone: +49 6192 401 104 Fax: +49 6192 401 105 info.sg@sto.com www.sto-sea.com

<sup>\*</sup>Product images may differ from the actual product.