


# Technical Data Sheet

## StoPrim Plex

Water-based acrylate deep-acting primer, tested for harmful substances



### Characteristics

#### Area of application

- Exterior and interior
- On mineral and organic substrates and coatings
- For consolidating chalky but load-bearing existing paint coats and crumbling renders
- For reducing the absorption capacity of gypsum plasterboards, porous and absorbent substrates, e.g. plasters, renders, unfired masonry or cellular concrete

#### Properties

- Absorbency-regulating
- Surface-consolidating
- Adhesion-promoting
- Solvent and plasticiser-free
- Low-emission
- TÜV seal of quality - externally monitored

### Technical Data

Criteria	Standard / test specification	Value/ Unit	Notes
Density	EN ISO 2811	1.0 g/cm <sup>3</sup>	

The characteristic values stated are average values or approximate values. Due to the natural raw materials in our products, the stated values can vary slightly in the same delivery batch; this does not affect the suitability of the product for its intended use.

### Substrate

#### Requirements

The substrate must be firm, dry, clean, load-bearing, and free from sinter layers, efflorescence and release agents.

#### Preparations

Check existing coatings for their load-bearing capacity. Remove any non-load bearing or structurally weak coatings.

### Application

#### Application temperature

Lowest temperature of substrate / air : +5°C  
Highest temperature of substrate / air: +30°C

#### Material preparation

Before applying the material, shake it thoroughly in its original container. Depending on the absorption capacity of the substrate, the product is dilutable with water up to a mixing ration of 1:1.

#### Consumption

Type of application	Approx. consumption
Per paint coat	0.10 - 0.40 lit/m <sup>2</sup>

Material consumption depends on the application, substrate, and consistency, among other factors. The stated consumption values are only to be used as a guide. If required, determine precise consumption values on the basis of the specific project.

# Technical Data Sheet

## StoPrim Plex

**Application** By paint brush, by roller, by airless sprayer  
 Apply the material, e.g. with a block brush and work it in, or spray on with an airless sprayer, e.g. an inoSPRAY device.  
 Take appropriate measures for protection against spray fog. Prime coatings must not form a glossy layer.

**Drying, curing, ready for next coat** The product dries physically, in that water evaporates.  
 High humidity, low air exchange, and low temperatures prolong the drying time.  
 At +20°C temperature (air and substrate) and 65% relative air humidity: over-coatable after approx. 12 hours.

**Cleaning the tools** Tools must be cleaned immediately after use with cleaning water

**Notes, recommendations, special information, miscellaneous** Take appropriate measures for protection against spray fog.  
 Please consult the local sales office for further information and any site assistance required.

### Delivery

**Colour** Colourless

Packaging	Article number	Name	Packing
	00518-002	StoPrim Plex	20 lit

### Storage

**Storage conditions** Store in cool dry conditions; avoid direct sunlight.

**Storage life** The quality of the material in its original container is guaranteed for the maximum stated storage life. The storage life information is included in the batch number on the container.  
 Batch number explanation:  
 Number 1 = the last number of year, numbers 2 + 3 = a week  
 I.e.: 1450013223 – stock date until the 45th week of the year 2021

### Identification

**Product group** Primer

**Safety** Please refer to Safety Data Sheet.

### Special Notes

The information in this Technical Data Sheet serves to ensure the product's intended use, or its suitability for use, and is based on our findings and experience. Users are nevertheless responsible for establishing the product's suitability and use.

Applications not specifically mentioned in this Technical Data Sheet are permissible only after prior consultation. Where no approval is given, such applications are at the user's own risk. This applies in particular when the product is used in combination with other products.

When a new Technical Data Sheet is published, all previous Technical Data Sheets are no longer valid. The latest version is available on [www.sto-sea.com](http://www.sto-sea.com).

## Technical Data Sheet

---

### StoPrim Plex

**Sto SEA Pte Ltd**  
159 Sin Ming Road  
#06-02 Amtech Building  
Singapore 575625  
Phone: +65 6453 3080  
Fax : +65 6453 3543  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**Sto SEA Sdn Bhd**  
28, Jalan Rajawali 3  
Bandar Puchong Jaya,  
47170 Selangor, Malaysia  
Phone: +60 3 8080 9066  
Fax: +60 3 8080 9255  
[info.my@sto.com](mailto:info.my@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**Sto SEA Pte Ltd**  
3656/49-52 Green Tower, 16<sup>th</sup> Floor  
Rama IV Rd, Klongton, Klongtoei,  
10110 Bangkok, Thailand  
Phone: +66 2 1684 921 Ext. 230  
Fax: +66 2 1684 999  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

**Sto SE & Co. KGaA**  
Ehrenbachstr.1  
79780 Stühlingen,  
Germany  
Phone: +49 7744 57-0  
Fax: +49 7744 57-2178  
[info.sg@sto.com](mailto:info.sg@sto.com)  
[www.sto-sea.com](http://www.sto-sea.com)

\*Product images may differ from the actual product.